

538275
Rec'd PCT/PT 10 JUN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/538275



(43) International Publication Date
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number
WO 2004/053973 A1

(51) International Patent Classification⁷: H01L 21/56,
23/28, 23/31, 23/495

Elstan, Anthony [IN/SG]; Blk 105 Aljunied Cres-
cent, #02-221, Singapore 380105 (SG). YEONG, Kok,
Cheong, Bernard [SG/SG]; Blk 574 Hougang St. 51
#08-07, Singapore 530574 (SG).

(21) International Application Number:
PCT/SG2002/000288

(74) Agent: WATKIN, Timothy, Lawrence, Harvey; Lloyd
Wise, Tanjong Pagar, P O Box 636, Singapore 910816
(GB).

(22) International Filing Date:
10 December 2002 (10.12.2002)

(25) Filing Language: English

(81) Designated States (national): DE, SG, US.

(26) Publication Language: English

Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv)) for US only

(71) Applicant (for all designated States except US): IN-
FINEON TECHNOLOGIES AG [DE/DE]; St.-Mar-
tin-Strasse 53, 81669 München (DE).


Published:
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (for US only): FERNANDEZ,

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF PACKAGING INTEGRATED CIRCUITS AND INTEGRATED CIRCUIT PACKAGE PRODUCED BY
THE METHOD



(57) Abstract: A method of packaging integrated circuits is proposed in which two integrated circuits 13, 17 are provided in register on opposite sides of a single substrate 1. Electrical contacts on the each of the integrated circuits 13, 17 are electrically connected to electrical conductors of the substrate 1. One of the integrated circuits 17 may be wire bonded to the substrate, while the other is a flip-chip 13. Holes 7 are provided through the substrate 1 so that in a moulding operation a single resin body 21 may be formed encasing both of the integrated circuits 13, 17 by applying resin only to an upper side of the substrate 1 and allowing the resin to flow to the other side of the substrate 1 into a volume defined by a box 15.

WO 2004/053973 A1

Method of packaging integrated circuits, and integrated circuit
packages produced by the method

Field of the invention

The present invention relates to methods of packaging integrated circuits, and
5 integrated circuits produced using the method.

Background of Invention

It is well known to provide integrated circuits packages in which integrated
circuits (dies) are located within resin bodies. Electrical contacts of the each
integrated circuit are electrically in contact with corresponding electrical
10 conductors which protrude out of the resin body.

In one type of package, the integrated circuits are located on a die pad portion
of a lead frame with the electric contacts facing away from the lead frame, and
wires are formed between the electric contacts and respective lead fingers of
the lead frame. The resin is applied to encase the integrated circuits and the
15 wires in the resin body, leaving a portion of the lead frames protruding from
the resin body. The lead fingers are then cut to separate them from the
remainder of the lead frame, and thus singulate the packages.

An alternative type of integrated circuit is called a "flip chip" which is
positioned on (and normally adhered to) a substrate (a term which will be
20 used very generally here, for example to include also a lead frame) with the
electrical contacts facing the substrate, and in electrical contact with
corresponding electric contacts provided in the substrate. The electric
contacts on the substrate are typically electrically connected to electrically
conductive paths formed through the material of the substrate. The flip-chip is
25 typically encased in a resin body which secures it to the substrate to form a
package.

There is pressure to improve integrated circuits packages to increase the number of input/output connections (I/Os), reduce the package footprint, reduce the package thickness and improve the thermal management (that is, reduce the risk of the integrated circuit overheating).

- 5 Various proposals have been made to do this, typically proposing that a plurality of dies are packaged into a single package. For example, it is known to provide a plurality of dies inside a single package stacked one above the other with an adhesive paste between them. It is further known to provide two dies placed side by side (e.g. on a lead frame) within a single resin body.
- 10 One disadvantage with providing a stacked die package assembly is that the thickness of the package is increased. Additionally, there are reliability concerns due to the presence of the adhesive layer between the dies, and due to the reduced possibilities for heat dissipation which in turn lead to an increased risk of overheating.
- 15 Conversely, providing the dies side by side means that the footprint of the package is increased.

Summary of the Invention

- 20 The present invention aims to provide new and useful methods for packaging integrated circuits, and integrated circuit packages produced using the methods.

In general terms, the present invention proposes that two integrated circuits are provided in register on opposite sides of a single substrate and that electrical contacts on the both of the dies are electrically connected to electrical contacts of the substrate.

- 25 Conventional moulding techniques are not well adapted for applying resin simultaneously to both sides of a substrate, so that if the invention is

implemented using conventional techniques two successive moulding operations would be required, each forming a resin body on a respective side of the sides of the substrate. This would significantly complicate the complexity of the moulding. For that reason, the substrate is preferably
5 provided with holes through which resin can flow during a moulding operation, so that both of the integrated circuits can be encased in a single resin body during a single moulding operation in which resin is applied to only one side of the substrate (e.g. the upper side).

During the moulding operation a moulding element should be provided to
10 define a cup enclosing the lower integrated circuit, and thereby define the shape of the portion of the resin body on the lower surface of the substrate.

This moulding element may be formed as a portion of a mould in which the substrate and integrated circuits are located during the moulding operation. However, more preferably, the moulding element may be a box element which
15 is permanently connected to the substrate (e.g. by the moulding operation itself) and which remains in the completed package.

Preferably, at least one of the integrated circuits is provided as a flip chip. For example, one of the integrated circuits may be a flip-chip and the other an integrated circuit requiring wire bonding.

20 One of the integrated circuits may be provided on the same side of the substrate as eutectic solder balls which provide electrical contacts out of the substrate. In this case, the eutectic solder balls may be arranged on a surface of the substrate in an array including at least one opening, and the integrated circuit may be provided in the openings.

25 This is particularly suitable in the case that the integrated circuit which is provided on the same side of the substrate as the eutectic solder balls is a flip-chip. Since a flip-chip does not include wire bonds, it can be packaged

with a thinner resin body than an integrated circuit which includes wire bonds. Preferably the portion of the resin body on this side of the substrate, and the box if one is provided, extend from the substrate by a distance which is less than the maximum distance to which the eutectic balls extend from the substrate. To make this easier to achieve the integrated circuit on this side of the substrate may be provided in a recess in the substrate. Preferably the recess exposes electrical elements in the substrate to which the integrated circuit is connected.

The resin moulding process may optionally be performed in a vacuum, to avoid the risk of pockets of ambient atmosphere gases (air) being trapped in the resin body. Alternatively, this can be achieved by a proper design of the moulding arrangement. For example, in the case that resin is applied from the upper side of the substrate and is intended to flow through the holes to the lower side of the substrate, the box (or other moulding element) at the lower side of the substrate may include openings to allow the air to escape.

Brief Description of The Figures

Preferred features of the invention will now be described, for the sake of illustration only, with reference to the following figures in which:

Fig. 1 is a view of a first surface of a substrate for use in a method which is an embodiment of the invention;

Fig. 2 is a cross-sectional view illustrating a moment during the implementation of the packaging method of Fig. 1;

Fig. 3 is a cross sectional view of package produced by the method of Fig. 1;

Fig. 4 is an exploded view of the package of Fig. 3.

Detailed Description of the embodiments

Referring firstly to Fig. 1, a substrate 1 for use in a method which is an embodiment of the invention is a planar member which includes a first surface on which a plurality of solder balls 3 are arranged in a rectangular array. The array includes regions 5 in which there are no solder balls 3. In each of these regions 5 are four holes 7 which extend through the substrate 1 perpendicular to the plane of the substrate. The regions 5 further include respective central portions 9 having bump openings for contacting respective electrical contacts on a flip-chip which will be located over them. As in conventional substrates, the substrate 1 includes indexing holes 11 to help in positioning the substrate 1 in relation to the integrated circuits and moulding apparatus.

In a first step of the assembly process a flip-chip 13 (shown in Fig. 2, which is a cross section is a plane including two of the holes 7) is attached to each of the regions 9 with its electrical contacts in contact with the bump openings, and a box 15 having an opening is connected to the substrate 1 with the opening facing towards the flip chip 13, so that the box defines a cup enclosing the flip-chip 13. The box 15 may be formed of copper or gold, and may be adhered to the substrate 1. A second integrated circuit 17 is adhered to the opposite face of the substrate 1 (i.e. the one not shown in Fig. 1) and wires 19 are formed between electrical contacts on the second integrated circuit 17 and corresponding electrical contacts on the upper surface of the substrate 1.

The assembly thus formed is shown in cross-section in Fig. 2. As shown in this figure, the substrate 1 includes layers 19 in which electrical connections are provided, sandwiched by insulating layers. The construction of such layers will be familiar to one skilled in flip-chip technology. The contacts of the flip-chip make direct contact to electrical leads in the portion of the layer 19 exposed by the recess 18. Furthermore, as is clear from Fig. 2, the portions 9 of the regions 5 are located within recesses 18 in the lower surface of the

substrate 1, so that the surface of the box 15 which is furthestmost from the substrate 1 (i.e. lowest in Fig. 2) is still closer to the substrate 1 than the lowest parts of the solder balls 3.

5 The assembly is then positioned in a conventional moulding device in the orientation shown in Fig. 2. The moulding device applies resin to the upper surface of the substrate to create a resin body 21 including a portion 23 on the upper surface of the substrate 1 having a shape defined by the shape of a mould of the moulding device. During this moulding process, resin flows
10 through the holes 7 into the volume defined by the box 15 and fills that box, so that the resin body 21 further includes a portion 25 on the lower surface of the substrate 1 defined by the internal shape of the box 15. The integrated circuit package thus formed is shown in Fig. 3.

15 Although not shown in Fig. 3, the box 15 may include openings to ensure that any air which is present in the box 15 before the moulding operation begins is not trapped there in pockets. The openings provide exit paths. Alternatively, the method can be performed at low pressure (e.g. much less than one atmosphere).

20

Fig. 4 is a view of the package exploded in the direction marked A in Fig. 3 with the substrate 1 divided into two along one of the planes 19.

Although only a single embodiment of the invention has been shown, many
25 variations are possible within the scope of the invention as will be clear to a skilled reader. For example, the provision of the box 15 is not necessary to the invention, and the shape of the portion 25 of the resin body may instead be defined by a mould which is attached to the lower face of the substrate 1 during the moulding operation and subsequently removed. Furthermore, in
30 alternative embodiments of the invention, the resin may be supplied from

under the substrate 1, although this possibility increases the complexity of the operation and is not presently preferred.

Claims

1. A method of packaging integrated circuits comprising:

attaching a first integrated circuit to a first face of an substrate with
electrical connection between corresponding contacts of the substrate and the
5 first integrated circuit;

attaching a second integrated circuit to a second face of an substrate
with electrical connection between electrical contacts of the substrate and the
second integrated circuit; and

a moulding step in which the first and second integrated circuits are
10 encased in resin.
2. A method according to claim 1 in which the substrate includes holes
extending between the faces, the encasing step including applying resin to a
first side of the substrate, the resin flowing through the holes to the second
side of the substrate, whereby the resin forms a single resin body encasing
15 both of the integrated circuits.
3. A method according to claim 2 in which, before said moulding step, a
box is attached to the second side of the substrate defining a volume for
receiving resin.
4. A method according to claim 3 in which the box includes openings
20 defining exit paths for gas within the box.
5. A method according to any preceding claim in which the moulding step
is performed at a pressure of less than one atmosphere.
6. A method according to any preceding claim in which the substrate is
laminar having at least one face which includes solder balls, the moulding
25 step forming resin on that face having a maximum distance from the plane of

said substrate which is smaller than the maximum extension of the solder balls from the plane of the substrate.

7. A method according to claim 6 in which the solder balls are arranged in an array having a region without solder balls, the integrated circuit
5 corresponding to that side of the substrate being located in said region.

8. A method according to any preceding claim in which at least one of the integrated circuits is a flip chip.

9. A method according to claim 8, when dependent on claim 6 or claim 7, in which the flip chip is located on the face of the substrate which includes the
10 solder balls.

10. A method according to claim 8 in which the flip chip is located in a recessed portion of the substrate.

11. A method according to any preceding claim in which the electrical contacts of at least one of the integrated circuits are connected to electric
15 contacts on the substrate by wire bonding.

12. A package produced by a method according to any of claims 1 to 11.

13. A substrate for use in a method according to any preceding claim.

14. An integrated circuit package comprising a substrate including electrical contacts and integrated circuits attached to opposite sides of the
20 substrate with their electrical contacts electrically connected to corresponding electrical contacts on the substrate, each of the integrated circuits being encased in resin.

15. An integrated circuit package according to claim 14 in which a single resin body encases both the integrated circuits and extends through holes in
25 the substrate.

FIG 1




FIG 2




FIG 3





FIG 4



INTERNATIONAL SEARCH REPORT

International Application No

PCT/SG 02/00288

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H01L21/56 H01L23/28 H01L23/31 H01L23/495

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal, WPI Data, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 365 963 B1 (SHIMADA TOSHIYASU) 2 April 2002 (2002-04-02) abstract	1-15
A	US 6 038 136 A (WEBER PATRICK O) 14 March 2000 (2000-03-14) abstract	1-15
A	US 5 697 148 A (DOOT ROBERT KENNETH ET AL) 16 December 1997 (1997-12-16) abstract	1-15

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

14 July 2003

Date of mailing of the international search report

06. 08. 2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

ERIK MILIANDER/JA A

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/SG 02/00288

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 6365963	B1	02-04-2002	JP	2001077293 A	23-03-2001
US 6038136	A	14-03-2000	WO	0070678 A1	23-11-2000
			US	2001038166 A1	08-11-2001
			US	6157086 A	05-12-2000
			US	6324069 B1	27-11-2001
			US	2002043721 A1	18-04-2002
			EP	1190448 A1	27-03-2002
			JP	2003500833 T	07-01-2003
US 5697148	A	16-12-1997	NONE		